
# BETTER HOME PRODUCTS

## PACIFICA COLLECTION SPECIFICATIONS

## MATTE BLACK FINISH



## BHP ITEM# 99144BLK - Passage Set

Grade III tubular passage set. Solid zinc cast construction.


Door Prep - Crossbore 2 1/8", Edge Bore 1", Latch Face 1"x2 1/4"


Door Thickness - 1 3/8" to 1 3/4"

Function: Both levers always free

**Strike** - Full lip radius corner standard. Other options available **Latch** - 1/2" throw bolt, 2 3/8" or 2 3/4" backset adjustable. Radius

corner face plate standard. Other options available **Door Handing** - Non-handed






# BHP ITEM# 99244BLK - Privacy Set


Grade III tubular privacy set. Solid zinc cast construction.

Door Prep - Crossbore 2 1/8", Edge Bore 1", Latch Face 1"x2 1/4"

Door Thickness - 1 3/8" to 1 3/4"

Function - Outside lever locked by push button inside, inside lever always free. Also can be opened by emergency key out side Strike - Full lip radius corner standard. Other options available Latch - 1/2" throw bolt, 2 3/8" or 2 3/4" backset adjustable. Radius corner face plate standard. Other options available





# (BHP) ITEM# 99344BLK - Dummy Lever


Grade III dummy lever. Solid zinc cast construction.


**Door Prep** - Surface mounted with 2 exposed mounting screws. No door prep needed

Door Thickness - greater than 1"

Function: Fixed lever, for doors where only a pull / push is required.

Door Handing - Non-handed





#### **BHP** ITEM# 99944BLK - Handleset Trim Lever


Grade III handleset trim lever, works for all BHP offering handlesets. Solid zinc cast construction.


Door Prep - See BHP handleset door prep

Door Thickness - 1 3/8" to 1 3/4" Function: Lever always free Door Handing - Non-handed

\*\* Packed with a square shape style match deadbolt backplate for

handleset





#### (BHP) ITEM# 99544BLK - Entry Set

All metal components with inner anti-pick shield

Door Prep - Crossbore 2 1/8", Edge Bore 1", Latch Face 1"x2 1/4"

Door Thickness - 1 3/8" to 1 3/4"

Function: Locked or unlocked by key out side or turn-piece inside.

Cylinder - 5 pin KW1 keyway. Other options available

Strike - Full lip radius corner standard. Other options available

Latch - 1/2" throw bolt, 2 3/8" or 2 3/4" backset adjustable. Radius

corner face plate standard. Other options available

Door Handing - Non-handed