



BETTER HOME PRODUCTS

LOW - PROFILE DEADBOLT SPECIFICATIONS



20 Minute Fire Rating

BHP ITEM# ULSK10688CH Chrome
 ULSK10615SN Satin Nickel
 ULSK10611DB Dark Bronze
 ULSK10644BLK Matte Black
 ULSK10604SB Satin Brass



Door Prep - Crossbore 2 1/8", Edge Bore 1", Latch Face 1"x2 1/4"
Door Thickness - 1 3/8" to 1 3/4"

Function: Locked or unlocked by key out side or turn-piece inside. inside always free

Cylinder - 5 pin KW1 keyway. Other options available

Strike - Packed with 1 Pc 1x 2 1/4" radius corner strike and 1 Pc full lip radius corner strike. Other options available

Latch - 1" throw bolt, 2 3/8" or 2 3/4" backset adjustable. Radius corner face plate standard. Other options available



20 Minute Fire Rating

BHP ITEM# ULSK10888CH Chrome
 ULSK10815SN Satin Nickel
 ULSK10811DB Dark Bronze
 ULSK10844BLK Matte Black



Door Prep - One side bore 2 1/8" dia", Edge Bore 1".

Door Thickness - 1 3/8" to 1 3/4"

Function: Locked or unlocked by turn-piece inside.

Strike - Packed with 1 Pc 1 x 2 1/4" radius corner strike and 1 Pc full lip radius corner strike. Other options available

Latch - 1" throw bolt, 2 3/8" or 2 3/4" backset adjustable. Radius corner face plate standard. Other options available



20 Minute Fire Rating

BHP ITEM# ULTIB10688CH Chrome
 ULTIB10615SN Satin Nickel
 ULTIB10611DB Dark Bronze
 ULTIB10644BLK Matte Black
 ULTIB10604SB Satin Brass

Door Prep - Crossbore 2 1/8", Edge Bore 1", Latch Face 1"x2 1/4"



Door Thickness - 1 3/8" to 1 3/4"

Function: Locked or unlocked by key out side or turn-piece inside. inside always free

Cylinder - 5 pin KW1 keyway. Other options available

Strike - Packed with 1 Pc 1 x 2 1/4" radius corner strike and 1 Pc full lip radius corner strike. Other options available

Latch - 1" throw bolt, 2 3/8" or 2 3/4" backset adjustable. Radius corner face plate standard. Other options available



20 Minute Fire Rating

BHP ITEM# ULTIB10888CH Chrome
 ULTIB10815SN Satin Nickel
 ULTIB10811DB Dark Bronze
 ULTIB10844BLK Matte Black

Door Prep - One side bore 2 1/8", Edge Bore 1"

Door Thickness - 1 3/8" to 1 3/4"

Function: Locked or unlocked by turn-piece inside.

Strike - Packed with 1 Pc 1 x 2 1/4" radius corner strike and 1 Pc full lip radius corner strike. Other options available

Latch - 1" throw bolt, 2 3/8" or 2 3/4" backset adjustable. Radius corner face plate standard. Other options available